

DIE (OD X CLR) ROUND TUBE	LENGTH BETWEEN BENDS	AVAILABLE WALL THICKNESS		
1/2" (.50) x 1.5 CLR	1.125"	0.065	-	-
5/8" (.625) X 1.5 CLR	2.000"	0.065	-	-
3/4" (.75) X 2 CLR	1.625"	0.065	-	-
7/8" (.875) X 2 1/2 CLR	1.125"	0.065	-	-
1.0 X 2 7/16" CLR	3.125"	0.065	-	-
1.0 X 3" CLR	3.125"	0.065	-	-
1.0 X 6" CLR	3.125"	0.065	-	-
1.0 X 7" CLR	3.625"	0.065	-	-
1 1/8" (1.125) X 2 1/4" CLR	3.125"	0.065	-	-
1 1/8" (1.125) X 3" CLR	3.125"	0.065	-	-
1 1/4" (1.25) X 2" CLR (Stainless Steel)	2.625"	0.065	0.083 (AZ, AL)	-
1 1/2" (1.50) x 1 1/2" CLR	6.125"	0.065	-	0.125 (AZ, AL)
1 1/2" (1.50) x 1 3/4" CLR	3.000"	0.065	-	0.125 (AZ, AL)
1 1/2" (1.50) x 2 3/4" CLR	4.000"	0.065	-	0.125 (AZ, AL)
1 5/8" (1.625) X 2 1/2" CLR	4.125"	0.065	-	-
1 3/4" (1.75) X 3" CLR	4.625"	0.065	-	-
1 7/8" (1.875) X 3 3/4" CLR	3.875"	0.065	-	-
2" X 2" CLR	6.000"	0.065	.083 (SS, MS)	0.125 (SS, MS)
2" X 2 3/4" CLR	4.125"	0.065	.083 (SS, MS)	0.125 (SS, MS)
2" X 4" CLR	6.125"	0.065	.083 (SS, MS)	0.125 (SS, MS)
2 1/4" (2.25) X 2 1/2" CLR	4.500"	0.065	-	-
2 1/4" (2.25) X 3" CLR	4.500"	0.065	-	-
2 1/4" (2.25) X 3" CLR (CNC Bend)	6.125"	0.065	-	-
2 1/2" (2.50) X 2 1/2" CLR	5.125"	0.065	0.083 (AZ, AL)	0.125
2 1/2" (2.50) X 3" CLR	5.125"	0.065	0.083 (AZ, AL)	0.125
2 1/2" (2.50) X 3" CLR (CNC Bend)	6.125"	0.065	0.083 (AZ, AL)	0.125
2 1/2" (2.50) X 3 1/2" CLR (CNC Bend)	6.125"	0.065	0.083 (AZ, AL)	0.125
2 1/2" (2.50) X 5" CLR	6.000"	0.065	0.083 (AZ, AL)	0.125
3" X 3" CLR	9.000"	0.065	0.078 (SS, MS)	0.125 (SS, MS)
3" X 3 1/2" CLR	6.000"	0.065	0.078 (SS, MS)	0.125 (SS, MS)
3" X 4 1/2" CLR	6.000"	0.065	0.078 (SS, MS)	0.125 (SS, MS)
3" X 6" CLR	6.000"	0.065	0.078 (SS, MS)	0.125 (SS, MS)
3 1/2" (3.50) X 4" CLR	10.000"	0.065	-	0.125
3 1/2" (3.50) X 6" CLR	10.000"	0.065	-	0.125
4" X 4" CLR	12.000"	0.065	0.083	-
4" X 4 1/2" CLR	6.000"	0.065	0.083	-
4" X 6" CLR	10.000"	0.065	0.083	-
4 1/2" (4.50) X 6" CLR	13.500"	0.065	-	0.125 (AZ, AL)
5" X 5 1/2" CLR	10.000"	0.065	0.083	-
5" X 7" CLR	10.000"	0.065	0.083	-
6" X 7" CLR	18.000"	0.065	0.083	-